

LINE

BRENT GRAY

Ultra-premium 9-inch boots. Perfect fit and comfort. Exclusive design. State-of-the-art technology and components.



TECHNOLOGIES

■ IPD TECHNOLOGY

Progressive density increase. High comfort, optimum cushioning in the heel area and maximum stability in the step.

ANTITORSION INSERT

Highly dense semi rigid TPU insert. Controls unwanted twisting and protects the arch of the foot.

■ REFLEMAX

High visibility reflective material that provides extra safety in adverse weather conditions and in those moments of the day where the lights are dimmer.

AIRCORE

High technology lining, three layer with permanent airflow air chamber.

■ FOAMFREE

Inside linings without synthetic foam support. It reduces moisture, and increases comfort.

DCP SYSTEM

System of high-density TPU double insert which significantly increases resistance to abrasion and grip.

SHOCK ABSORBER

Programmed deformation ovoidal vault system. It redirects the load on the cue by distributing it evenly.

DURATEX

Fabric with high abrasion and flexion resistance.

■ MICROTEC PRO

Effective antimicrobial protection. Prevents the development of microorganisms and bad odors.

FUNCIONAL



SUELA P.U.- MULTIDENSIDAD
ULTRAPREMIUM
BRENT GRAY

DESCRIPTION

Model: 9-inch Boot

UPPER COMPOUND

Color

• Gray

Upper

- Combination of Leather and Textile Fabrics
- Curried Full-Grain Leather

Inside

AIRCORE lining (lower part)

Collar

Padded

Tongue

• With Bellows, Lined and Padded

■ TOE CAP

• Steel

ACCESORIES

Laces

• Ultra Tensile Strenght with REFLEMAX

Lace-keepers

- High-Endurance Composite, Closed (non-metallic)
- High-endurance composite, open (non-metallic)

Insoles

• Ultra-comfortable, ergonomic, conformed insole

PLANT

Other properties

- Electrical Hazard
- Resistant to Hydrocarbons
- Slip Resistant
- Self-Cleaning
- Resistant to Flexing
- Resistant to Abrasion
- Grooves for Stair-Climbing
- Wide Tread Base

Compound

• Multidensity Polyurethane

Upper plant adhesion

· Direct injection

OPTIONALS

• PR - Puncture Resistant

SIZES

From 6.5 to 13

SAFETY HAZARDS SPECIFICATIONS



Last review date: 2022/07/22

WWW.FUNCIONALWEB.COM

The content of this document can be changed without previous notice.

© Maincal 2024